MAIN CONTROL BOX

특징

- 당사에서 생산되는 캐터필라 CW360B-1000, CW350B-350을 연결하여 장비의 작동을 관장하는 컨트롤 박스입니다.
- 지중 포설을 위하여 맨홀에 들어갈 수 있는 사이즈로 제작 되었습니다.
- 옵션으로는 캐터필라 속도조절형(INVERTER 내장) 타입이 있습니다.

Model No.	Capacity	Power Source	Dimension(mm)	Weight(kg)
120-03004 (CW-MC30N)	30kW	AC 220V 60Hz, 3Phase	420L*420W*660H	55
120-03004 (CW-MC50N)	50kW		420L*420W*800H	70

CONNECTOR BOX & POWER CABLE

258-2 SIMOKECHEON-RO, HYEONDO-MYEON, SEOWON-GU, CHEONGJU-SI, CHUNGBUK-DO, 363-823, KOREA
TEL/FAX : +82-(0)43-269-1116 / +82-(0)43-269-1183. E-MAIL:CWSE@CWSE.CO.KR

CONNECTOR BOX -BASIC (Model No. : CWCA2, CWCA3)

CWCA2	Power in-out
CWCA3	Power in - Junction out
Dimensions(LxWxH)	200x200x150 mm
Weight	4 kg

CONNECTOR BOX -OPTION 1 (Model No. : CWCA2-1, CWCA3-1)

CWCA2	Power in-out
CWCA3	Power in - Junction out
Dimensions(LxWxH)	200x200x150 mm
Weight	4.5 kg

CONNECTOR BOX -OPTION 2 (Model No. : CWCA2-2, CWCA3-2)

CWCA2	Power in-out
CWCA3	Power in - Junction out
Dimensions(LxWxH)	200x200x150 mm
Weight	5 kg

POWER CABLE (Model No. : 120-03006)

Cable	600VCT 10SQx4 Pin
Dimension(Length)	30 m
Weight	8 kg

258-2 SIMOKECHEON-RO, HYEONDO-MYEON, SEOWON-GU, CHEONGJU-SI, CHUNGBUK-DO, 363-823, KOREA
TEL/FAX : +82-(0)43-269-1116 / +82-(0)43-269-1183. E-MAIL:CWSE@CWSE.CO.KR