


SAS ROPE

SAS-3 POWER

SAS-4 POWER



F3xSeS(39)+FC

F4xSeS(39)+FC

SPECIFICATION

(A Type : 165kg/mm², B Type : 180kg/mm², C Type : 195kg/mm²)

Diameter (mm)	Min. Breaking Load (ton)							
	F3xSeS(39)+FC			Weight (kg/m)	F4xSeS(39)+FC			Weight (kg/m)
	A Type	B Type	C Type		A Type	B Type	C Type	
12.6	10.2	11.1	12.0	0.647	9.53	10.4	11.3	0.653
14.0	12.6	13.7	14.9	0.799	11.8	12.8	13.9	0.806
16.0	16.4	17.9	19.4	1.043	15.4	16.8	18.2	1.053
18.0	20.8	22.7	24.6	1.320	19.4	21.2	23.0	1.333
19.0	23.2	25.3	27.4	1.471	21.7	23.6	25.6	1.485
20.0	25.7	28.0	30.4	1.630	24.0	26.2	28.4	1.645
22.4	32.2	35.2	38.1	2.045	30.1	32.8	35.6	2.064
24.0	37.0	40.4	43.7	2.347	34.6	37.7	40.9	2.369
26.0	43.4	47.4	51.3	2.755	40.6	44.3	47.9	2.781
28.0	50.3	54.9	59.5	3.195	47.0	51.3	55.6	3.225
32.0	65.8	71.7	77.7	4.173	61.5	67.0	72.6	4.212
35.0	78.7	85.8	93.0	4.992	73.5	80.2	86.9	5.039