

스틸 와이어 로프

6×24+7FC

For Marine and Engineering Purposes

Construction : 6Strands 24 Wires per Strand 7Fiber Cores



SPECIFICATION

Diameter	Min. Breaking load (ton)			Weight (kg/m)
mm	G Type (150kg/mm ²)	A Type (165kg/mm ²)	B Type (180kg/mm ²)	
8	2.98	3.21	3.5	0.212
9	3.77	4.06	4.43	0.269
9.5	4.2	4.53	4.94	0.300
10	4.65	5.02	5.47	0.332
11.2	5.83	6.3	6.87	0.416
12	6.7	7.23	7.88	0.478
12.6	7.38	7.97	8.69	0.527
13	7.86	8.48	9.25	0.561
14	9.12	9.84	10.7	0.651
14.3	9.51	10.3	11.2	0.679
15	10.5	11.3	12.3	0.747
16	11.9	12.8	14	0.850
17.5	14.2	15.4	16.8	1.017
18	15.1	16.3	17.7	1.076
19	16.8	18.1	19.8	1.199
20	18.6	20.1	21.9	1.328
21	20.5	22.1	24.1	1.464
22.4	23.3	25.2	27.5	1.666
24	26.8	28.9	31.5	1.912
25	29.1	31.4	34.2	2.075
25.4	30	32.4	35.3	2.142
26	31.4	33.9	37	2.244
28	36.5	39.3	42.9	2.603
28.6	38	41	44.8	2.716
30	41.9	45.2	49.3	2.988